

Fugapox Clean



Detergent for removing residues and halos of epoxy sealants.



Fields of application:

- concentrate detergent for removing residues of epoxy mortars and sealants like Fugapox and Fugapox Style, even if very resistant, from floors and walls;
- dilute 1:5 with water to remove halos of epoxy products;

- dilute 1:5 with water to enhance brightness of the grouting made with Fugapox Style;
- dilute 1:5 with water for remove dirt from ceramic tiles, marble, granites, lapped stoneware;
- professional use only;

Application:

to remove persistent residues of epoxy mortars or to clean porcelain stoneware, pour pure Fugapox Clean on the surface to be treated, and brush with a scrubber or an abrasive sponge, let it act for 10-15 minutes then rinse repeatedly with plenty of water. Proceed on small zones in case of big surfaces.

Persistent stains or incrustations can be cleaned by repeating this operation on the specific zones and with an forcible abrasive action. Recover the rinsing water and wait for the surface to be dried before any laying or

treatment. To remove marks of epoxy mortars again, pour Fugapox Clean 1:5 diluted with water, and repeat the actions described here above, as if it were persistent residues, letting it act only for some minutes.

Quality and Environmental Standards:

Fugapox Clean undergoes constant, careful testing at our laboratories, in compliance with the legislation in force - UNI EN ISO 9001/2015.

Warning:

- do not use on marbles or polished stones;
- rinse with plenty of water any treated surface;
- before carrying out the treatment, always do a preliminary test on the product to be treated, to verify it does not have any damage;
- use gloves and protective glasses during the treatment;
- before the use of product protect doors and windows, furniture, metallic or PVC profiles and all the surfaces that could be damaged from direct contact with the product.

Technical and application specifications

Hazard classification as per Directive 99/45/EC:	irritant
Application temperature:	from +5°C to +35°C
Color:	pale yellow
Aspect:	clear liquid
Product pH:	11
Specific weight g/cm ³ :	1.02
Harmonised customs code:	3402 90 90

Measurement of data at 23°C / 50% Residual Humidity and no ventilation. The data may be considerably modified by the conditions of use.

Characteristics	Application methods	Consumption
Removes halos from epoxy grouting Does not release harmful fumes or unpleasant smells Detergent suitable for lapped ceramics, too Dissolves hard epoxy residues	Manually	0.150 - 0.200 lt/m ²
		Storage
		Shelf life of 24 months in the original packages and in a fresh, dry place

Code	Product	Color	Packages	Pallet
2532301	Fungapox Clean	Transparent	1 lt x 10 pz	240 kg
2532300	Fungapox Clean	Transparent	10 lt	600 kg