

Legante Bianco

Pre-mixed white binder.



Fields of application:

- for exposed casts with relieves of colored aggregates;
- for sculptures, benches, flower boxes, vases, etc;
- for street furnishing elements;

- for various repairs;
- professional use only.

Characteristics:

Legante Bianco is made of selected cements with additives and high quality and precious aggregates, resulting in special application characteristics and a total white finish.

Application:

Mix **Legante Bianco** with aggregate and clean water till getting a well workable creamy paste.

Quality and Environmental Standards:

Legante Bianco undergoes constant, careful testing at our laboratories, in compliance with the legislation in force-UNI EN ISO 9001/2015.

Warning:

- do not apply in temperatures below +5°C or above +35°C;
- do not use for elastic joints;
- do not apply to frozen or thawing bases or those at risk of freezing during the 24 hours following application.

Technical and application specifications

Hazard classification as per Directive 99/45/EC:	none
Setting time (beginning):	≥ 75 minutes
Expansion:	≥ 10 mm
Application temperature:	from +5°C to +30°C

FINAL PERFORMANCE SPECIFICATIONS

Compression resistance after 7 days:	≥ 16 N/mm²
Compression resistance after 28 days:	≥ 32.5 N/mm²
Room/ambient temperature:	from -30°C to +90°C
Harmonised customs code:	38245090

Measurement of data at 23°C/50% Residual Humidity and no ventilation. The data may be considerably modified by the conditions of use.

Characteristics	Application methods	Consumption
Extra-white Ultra-fine Highly workable For indoor and outdoor application Granulometry: 0.1 mm		Depending on the use Storage Shelf life of 12 months in the original packages and in a fresh, dry place

Code	Product	Form and color	Packages	Pallet
401010	Legante Bianco	White powder	5 kg x 4 pcs	480 kg